



### Universal protective housing for infrared cameras of optris PI series



### Features:

- Environmental rating IP 66
- Additional air purge collar allows for a continuous operation in dusty and humid conditions
- Heating element and built-in fan enable for a 24/7 operation from -40 °C up to +60 °C
- Optional with integrated HD video camera with 1280 x 720 pixels for condition monitoring applications
- USB-Server Gigabit enables easy integration of both camera streams (IR + VIS) in video control systems

### Specifications Outdoor protective housing

Environmental rating	IP 66
Operating temperature range	-40 °C ... 50 °C (extended version: up to 60°C) <sup>1)</sup>
Heating	PTC heater (starts automatically at T < 15 °C) / Fan for homogeneous temperature distribution
Power supply	24 V DC (or PoE) <sup>2)</sup>
Power	70 W
Current draw	3 A (short term: 6 A)
Air purge collar	Integrated
Air pressure	Absolute pressure 1.1 bar at 20 – 100 l/min
Additional intergrable components	<ul style="list-style-type: none"> <li>• USB Server Gigabit (recommended for combination of PI and visual camera)</li> <li>• Industrial Process Interface (PIF)</li> </ul>
Material	Aluminum
Weight	2 kg / 2.5 kg with wall mount bracket
Max. FOV	90° (HFOV)
Accessories	Optional wall mount bracket <sup>3)</sup>

<sup>1)</sup> Extended version combinable only with PI450i with 27Hz and USB-Server HT.

<sup>2)</sup> PoE is not applicable for heater or fan.

<sup>3)</sup> The wall bracket is mandatory for mounting an optris outdoor protective housing.

### Specifications IR camera

Camera series	PI 400i/ 450i/ 640i/ 1M/ 05M/ 08M
Measurement ranges	from -20 °C up to 2450 °C
Optics FOV	from 4° to 90° HFOV (exchangeable lenses)
Power supply	USB/ PoE (via optional USB Server Gigabit)

### Specifications visual camera (optional)

Optical resolution	1280 x 720 pixels
Frame rate	30 Hz
Lens size	1/4"
Max. FOV	65° (DFOV)
Power supply	USB/ PoE (via optional USB Server Gigabit)

# Outdoor Protective Housing

## TECHNICAL DATA

Dimensions in mm

